
# Cal. JS20/JS55 Instruction manual

#### STOPWATCH FUNCTION: SMALL SECOND HAND TIME MEASUREMENT UP TO 29min 59sec.

- A) DISPLAYS AND BUTTONS
- B) SETTING THE TIME
- C) USING THE STOPWATCH
- D) STOPWATCH RESET (INC. AFTER REPLACING BATTERY)

## A) DISPLAYS AND BUTTONS



#### **B) SETTING THE TIME**

- 1. Pull the crown out to the 2nd Click Position.
- 2. Turn the crown to set hour and minute hands.
- 3. After the time has been set, push the crown back to the Normal position.

## C) SETTING THE DATE

- 1. Pull the crown out to the 1st Click Position.
- 2. Turn the crown clockwise to set the date.
- \* If the date is set between the hours of around 9:00 PM and 1:00 AM, the date may not change on the following day.
- 3. After the date has been set, push the crown back to the Normal position.


#### D) USING THE STOPWATCH

This stopwatch is able to measure and display time in 1/1 second united up to maximum of 30 minutes.

Stopwatch will stop automatically after running continuously for 30 minutes.

## [Measuring time with the stopwatch]

- 1. Press button "A" to start the stopwatch.
- 2. The stop watch can be started and stopped each time button "A" is pressed.
- 3. Pressing button "B" resets the stopwatch and stopwatch minute and second hands return to their Zero positions



## E) STOPWATCH RESET (INCL. AFTER REPLACING BATTERY)

This procedure should be performed when the stopwatch second & minute hand does not return to the Zero position.

- 1. Pull the crown out to the 2nd Click Position.
- 2. Press the button "A" to set the stopwatch second hand forward.

Press the button "B" to set the stopwatch second hand back.

- \* The stopwatch minutes hand is syncronized with stop watch second hand.
- \* The stopwatch second hand can be advanced rapidly by continuously pressing button "A" or "B".
- 3. Once the both hands been zeroed, reset the time and return the crown to its normal position.

These specifications might be changed without prior notice.